Forklift Seat Belts

Seat Belts for Forklift - Described in the Regulation guidelines are the application of operative restraints and seatbelts on forklifts. It says that the responsibility falls on the employers' to be able to make certain that each machinery, piece of equipment and device is utilized correctly used in accordance to the directions of the manufacturer.

With regards to their fabrication, use, design, maintenance and inspection Rough Terrain forklifts must satisfy the guidelines of ANSI Standard ASME B56.6-1992.

Side boom tractors and mobile machine with a Rollover Protective Structure, or ROPS for short, have to include seat belts that meet the requirements of the Society of Automotive Engineers, or SAE, Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whatever mobile machinery has seat belts required by law, the driver and subsequent passengers must ensure they make use of the belts each time the vehicle is in motion or engaged in operation in view of the fact that this could cause the machine to become unbalanced and therefore, unsafe.

When a seat belt or various operator restraint is needed on a lift truck.

While working a forklift, the seat belt requirements would depend on a number of factors. Contributing factors to this determination might include whether the lift truck is outfitted along with a Rollover Protective Structure, the type of forklift itself and the year the forklift was actually manufactured. The manufacturer's instructions and the requirements of the applicable standard are referenced in the Regulation.

With regards to powered industrial trucks, ANSI Standard ASME B56.1-1993 refers to an operator restraint device, system, or enclosure. A driver restraint device, system, or enclosure is intended in order to assist the operator in lessening the probability of entrapment of the head and/or torso between the truck and the ground in the event of a tip over. The restraint device or system may comprise a seat belt, even though a seat belt is not essentially a part of such equipment or system.